

# TECHNICAL MEMORANDUM

## Utah Coal Regulatory Program

---

May 2, 2005

TO: Internal File

THRU: D. Wayne Hedberg, Permit Supervisor

THRU: Wayne Western, Team Lead

FROM: Priscilla Burton, Environmental Scientist III/Soils

RE: Gob Vent Holes, Andalex Resources, Inc., Centennial Mine, C/007/0019 Task #2161 (2)

### **SUMMARY:**

The gob vent holes are located within the permit boundary on privately held surface in T. 12 S., R. 11 E. (p. 1-1 and Fig. 1-1, Aberdeen Mine GHV Proposed Location Map). Carbon County Soil Survey information indicates that vent holes fall within Map Unit 117 and 105.

Emergency GHV#1 is located in Map Unit 117. In a letter dated March 10, 2005, Division approval was granted for the emergency development of GVH#1. This review includes information for GVH#1, GVH #2, GVH#5, and GVH#6 which are all proposed to be drilled in April and May 2005.

---

TECHNICAL MEMO

---

**TECHNICAL ANALYSIS:**

## **ENVIRONMENTAL RESOURCE INFORMATION**

Regulatory Reference: Pub. L 95-87 Sections 507(b), 508(a), and 516(b); 30 CFR 783., et. al.

### **SOILS RESOURCE INFORMATION**

Regulatory Reference: 30 CFR 783.21; 30 CFR 817.22; 30 CFR 817.200(c); 30 CFR 823; R645-301-220; R645-301-411.

**Analysis:**

The gob vent holes are located within the permit boundary on privately held surface in T. 12 S., R.11 E. (p. 1-1 and Fig. 1-1, Aberdeen Mine GHV Proposed Location Map). Carbon County Soil Survey information indicates that vent holes fall within Map Units 117 (Trag-Beje – Senchert complex) and 105 (Senchert family-Senchert complex). Known soils resource information has been provided in Attachment 2-1 (Order 3 level information from the 1988 Carbon County Soil Survey) and an Order 1 Soil Survey of each site will be conducted as soon as ground conditions allow.

Senchert family soil is in the High Mountain Loam (Thurber Fescue) range site. The senchert soil is in the High Mountain Loam (Aspen) woodland site. The Trag-Beje-Senchert complex contains the Mountain Loam (Salina Wildrye)-Mountain Shallow Loam (Mountain Big Sagebrush)-High Mountain Loam (Aspen) woodland range sites. In a normal year production from all these range sites is expected to be between 1,200 and 1,500 lbs/ac dry weight. In a favorable year the productivity would be expected to increase to 2,000 lbs/ac dry wt. Attachment 3-1 provides more specific information for the gob vent hole productivity.

Based on the available information in the Carbon County Soil Survey, the Permittee understands that the soils to be disturbed are Mollisols, meaning they have a well developed, dark colored, base-rich topsoil horizon. For salvage purposes, a topsoil layer of 6 - 23 inches is realistic. And, the deeper soils may have a three inch layer of organic matter covering the surface. Depth to sandstone may vary from 20 – 60 inches.

**Findings:**

Information provided meets the requirements of Environmental Resources – Soils.

## **PRIME FARMLAND**

Regulatory Reference: 30 CFR 785.16, 823; R645-301-221, -302-270.

### **Analysis:**

The site is undeveloped rangeland at an elevation of 8,500 ft., with no developed water resources. There is no prime farmland at this location.

### **Findings:**

The Division finds that there is no prime farmland at the location of the gob vent holes.

## **OPERATION PLAN**

### **TOPSOIL AND SUBSOIL**

Regulatory Reference: 30 CFR Sec. 817.22; R645-301-230.

### **Analysis:**

#### **Topsoil Removal and Storage**

The plan indicates that a qualified person will be on site to ensure that the surface eighteen inches of topsoil will be salvaged from the 1.0 acre gob hole vent sites and placed in a topsoil stockpile. The layer from 18 – 24 inches in the profile will be removed and utilized in berms surrounding the site and the topsoil stockpiles. Thus, a total of 24 inches of surface soil will be stockpiled at the gob hole vent sites: approximately 2400 yds<sup>3</sup> in a stockpile and 30 yds<sup>3</sup> in berms. Topsoil will be removed in a single layer using a dozer. Topsoil stockpile dimensions are provided in Table 2-2.

Gob hole vent soils will be stockpiled temporarily for up to two weeks at a 1h:1v repose and most of the soil will be replaced after this time during contemporaneous reclamation of the drill pad. The remaining soil will be stockpiled at a 2h:1v slope until the degas wells are decommissioned and reclaimed. Soil stockpiled at 2h:1v will be seeded with the entire reclamation seed mix listed on p. 3-21, MRP. Soil storage in berms, as described in Section 232.500, will surround the pile and the perimeter of the site. The site will be fenced.

---

TECHNICAL MEMO

---

At the time of salvage, soils will be sampled for the parameters described in Section 243 to provide baseline information and to determine whether nutritive amendments are required at the time of reclamation.

Mud pit development will require further excavation as described in Section 231. Should bedrock be encountered before 15 ft, then multiple pits will be developed on the site or a portable mud pit will be employed.

**Findings:**

The information provided meets the requirements of R645-301-230 for topsoil and subsoil salvage.

## RECLAMATION PLAN

### TOPSOIL AND SUBSOIL

Regulatory Reference: 30 CFR Sec. 817.22; R645-301-240.

**Analysis:**

**Redistribution**

Section 341.200 indicates an 18 – 24 inch depth of ripping over the regarded site followed by an 18-inch topsoil replacement depth for contemporaneous and final reclamation (Section 242, Table 2-3). The topsoil will be left roughened in preparation of seeding.

The mud pits will be filled with a mixture of cuttings and subsoil. The cuttings will be covered with a minimum of four feet of soil, including the 18 inches of topsoil. The drilling method is by air and will produce little volume of liquid, however a foam will be used. (MSDA sheets on the foam are provided in Appendix X-1.)

**Findings:**

The information provided meets the requirements for topsoil and subsoil replacement.

## HYDROLOGIC INFORMATION

## TECHNICAL MEMO

---

Regulatory Reference: 30 CFR Sec. 773.17, 774.13, 784.14, 784.16, 784.29, 817.41, 817.42, 817.43, 817.45, 817.49, 817.56, 817.57; R645-300-140, -300-141, -300-142, -300-143, -300-144, -300-145, -300-146, -300-147, -300-147, -300-148, -301-512, -301-514, -301-521, -301-531, -301-532, -301-533, -301-536, -301-542, -301-720, -301-731, -301-732, -301-733, -301-742, -301-743, -301-750, -301-761, -301-764.

### Analysis:

#### **Acid- and Toxic-Forming Materials and Underground Development Waste**

##### **Gob Vent Holes Amendment X**

The drilling method is by air and will produce little volume of liquid, however a foam will be used. MSDA sheets on the foam are provided in Appendix X-1. The information indicates that appropriate measures (mud pit, berms) are being taken to ensure that the components of the drilling fluid are contained.

### Findings:

The information provided meets the requirements of R645-301-731.311 for identification and burial of acid/toxic forming materials.

## CONTEMPORANEOUS RECLAMATION

Regulatory Reference: 30 CFR Sec. 785.18, 817.100; R645-301-352, -301-553, -302-280, -302-281, -302-282, -302-283, -302-284.

### Analysis:

#### **General**

Figure 5-2 illustrates the portion of the site to be reclaimed contemporaneously within two weeks of drilling. Mud pits will be dried and cuttings will be mixed with excavated soils. The mixture of cuttings will be covered with four feet of soil, including the 18 inches of topsoil (Section 231.100). Section 341.200 describes the methods of surface reclamation.

### Findings:

The information provided meets the requirements for contemporaneous reclamation (R645-301-352) and sediment control as described in R645-301-532.

## STABILIZATION OF SURFACE AREAS

---

TECHNICAL MEMO

---

Regulatory Reference: 30 CFR Sec. 817.95; R645-301-244.

**Analysis:**

The topsoil stockpile will be left in a roughened state and seeded with the grasses, forbes, and shrubs found in the seed mix (Sec. 234.200). The mix includes great basin wildrye, bluebunch wheatgrass, slender wheatgrass, mountain brome (*Bromus inermis*), Indian ricegrass, and Sandberg bluegrass; all these species parallel the natives present in in soils map units 105 and 117 (1988 Carbon Co. Soil Survey).

Contemporaneous and final reclamation areas, the site will be roughened and the mix of grasses, forbes, and woody species given on page 3-21 of the MRP will be applied. The Permittee will apply a wood fiber mulch at 2,000 pounds per acre to all reclaimed areas as well.

If the grasses listed on page 3-21 of the MRP seed mix are not available, then the Permittee could substitute from the following list derived from the Carbon County Soil Survey for Map Unit 117:

Stipa (including Letterman needlegrass (*Stipa lettermanii*), needle and thread grass (*Stipa comata*), Columbia needlegrass (*Stipa columbiana*);  
Koeleria cristata or Prairie junegrass,  
Festuca thurberi or thurber fescue,  
Elymus glaucus or blue wildrye).

Outslopes of all gob vent access roads will be protected with vegetation and silt fences (Section 242 and Section 527.100). Rills and gullies will be repaired as described in section 244.300.

**Findings:**

The information provided in the application meets the requirements of R645-301-244 for soil stabilization.

**RECOMMENDATIONS:**

Approval is recommended.